

Land your orders with speed, care and smartness.



RAPIDO SSM (Stacking Sensitive Material) is the newly developed cut n' stack system from CIDAN machinery that speeds up your guillotine shear and never leaves you with scratches or dog-ears.

Set backgauge measurements

and number of cuts. The sheet support is pulled back fast as lightning and the cut material falls gently down onto the moveable material wagon (option) where the sheets are stacked at a speed of up to 24 panels per minute.

The material wagon can be loaded with up to 700kg. If you cut widths of up to 410mm you can stack to a height of 90mm, with widths greater than 410mm, to a height of 40mm.

In combination with the CutLink control system you have a real cutting and stacking giant that can be programmed for ten different backgauge settings in the desired quantities, all with neat stacking on the material wagon.


There is no smarter, gentler or more efficient backgauge system for high volumes.

The most important advantages:

- ✓ No scratches
- ✓ No dog-eared corners
- ✓ No customer complaints or recalls
- ✓ Fast, sensitive and structured stacking
- ✓ Extra suitable for sensitive materials
- ✓ Excellent ergonomics with no lifting



When the sheet support is pulled back, the sheets fall straight down for soft landing on the material wagon (option), with no risk of damage.



With RAPIDO SSM there is no heavy lifting. Your cut material is neatly stacked on the material wagon (option), ready for transfer to the next machine keeping panels at suitable working height.

Cutting speed

0–100 mm:	35 cuts/min but without SSM-function
125 mm:	24 cuts/min
750 mm:	15 cuts/min

Back gauge

Length	1000 mm
Drive system:	Two ball screws with Ø 25 mm two shaft with Ø 30 mm
Speed:	150 mm/seconds
Tolerance:	+/- 0.1 mm

 Find out more about RAPIDO SSM and see our demo film at <https://youtu.be/6H5zRFbngXM>

	Working length			Material thickness max			Outer dimensions			Weight
	mm	Steel ¹ mm	Stainless steel ² mm	Aluminum ³ mm	Length mm	Width mm	Height mm	kg		
Guillotine shear RAPIDO 32 SSM	3200	2.50	1.60	3.70	3907	2639	1583	2100		
Guillotine shear RAPIDO 41 SSM	4100	1.50	0.6	2.2	4807	2639	1583	2500		

Tensile strength ¹400 N/mm² ²600 N/mm² ³200 N/mm²

Option	Working width			Max load	Stacking height sheet width		Stacking height sheet width	
	Length mm	Width mm	Height mm		125–410 mm	410–1000 mm		
Material wagon, RAPIDO 32 SSM	3000	800	560	700	90	40		
Material wagon, RAPIDO 41 SSM	4010	800	560	700	90	40		

Dealer

CIDAN
MACHINERY GROUP

CIDAN Machinery Group markets and manufactures **CIDAN**, **Götene**, **Forstner** and **nulT**

CIDAN Machinery Sweden AB Box 28 • 533 21 GÖTENE • Tel: +46 (0)511 409 995 • info@cidanmachinery.com • www.cidanmachinery.com